

# ANCONA 2.0

N A S C O

# OUR ANCONA 2.0 COLLECTION

is filled with tiles that enhance the sense of movement thanks to a skilful blend of natural materials. When it comes to wood porcelain, there is no risk of monotony thanks to the colors that range from warm coffee to icy ocean gray. It is a collection that is guaranteed to build character into any room. Ancona 2.0 recreates a marquetry effect that exudes all the comfort of wood in a choice of five tones.



Ancona 2.0 Oak



Ancona 2.0 Grey Parquet

# TILES



**Chestnut**

8" x 30"  
8" x 48"



**Grey**

8" x 30"  
8" x 48"



**Maple**

8" x 30"  
8" x 48"



**Nutmeg**

8" x 30"  
8" x 48"



**Oak**

8" x 30"  
8" x 48"



**Chestnut Parquet**

24" x 24"



**Grey Parquet**

24" x 24"



**Oak Parquet**

24" x 24"



Ancona 2.0 Nutmeg Parquet



Ancona 2.0 Maple Parquet



Ancona 2.0 Chestnut



Ancona 2.0 Grey



Ancona 2.0 Oak

# TECHNICAL FEATURES



MODEL: **ANCONA 2.0**

SIZE: **20x120(F)**

THICKNESS(mm): **9**

DATE: **14/09/2021**

CODE: **017.241.0198.08972**

GROUP: **GROUP B1a UNE-EN 14411 Annex G / SASO ISO 13006:2018 Annex G**

TILE TYPE: **GL**

FINISH: **RECTIFIED MATT**

FAMILY: **PORCELAIN TILES (COLOURED BODY)**

NUMBER OF DESIGNS:

TEST	RESULT
 <b>UNE-EN ISO 10545-2</b> DIMENSIONAL FEATURES	<b>COMPLIES WITH THE STANDARD</b>
 <b>UNE-EN ISO 10545-3</b> WATER ABSORPTION	<b>&lt;= 0,5 %</b>
 <b>UNE-EN ISO 10545-4</b> MODULUS OF RUPTURE	<b>1600-2400 N</b>
 <b>N/mm<sup>2</sup></b> BREAKING STRENGTH	<b>35-45 N/mm<sup>2</sup></b>
 <b>UNE-EN ISO 10545-6</b> RESISTANCE TO DEEP ABRASION (MM <sup>3</sup> )	<b>&lt; 130 mm<sup>3</sup></b>
 <b>UNE-EN ISO 10545-7</b> RESISTANCE TO SURFACE ABRASION	<b>-</b>
 <b>UNE-EN ISO 10545-8</b> LINEAR THERMAL EXPANSION	<b>&lt;7,0 x 10<sup>-6</sup> °C<sup>-1</sup></b>
 <b>UNE-EN ISO 10545-9</b> THERMAL SHOCK RESISTANCE	<b>RESISTS</b>
 <b>UNE-EN ISO 10545-11</b> CRAZING RESISTANCE	<b>RESISTS</b>
 <b>UNE-EN ISO 10545-12</b> FROST RESISTANCE	<b>RESISTS</b>
 <b>UNE-EN ISO 10545-13</b> CHEMICAL RESISTANCE - AMMONIUM CHLORIDE 100 G/L	<b>A</b>
CHEMICAL RESISTANCE - SODIUM HYPOCHLORITE 20 MG/L	<b>A</b>
CHEMICAL RESISTANCE - HYDROCHLORIC ACID 3%	<b>COMPLIES WITH THE STANDARD</b>
CHEMICAL RESISTANCE - CITRIC ACID 100 G/L	<b>COMPLIES WITH THE STANDARD</b>
CHEMICAL RESISTANCE - POTASSIUM HYDROXYDE 30 G/L	<b>COMPLIES WITH THE STANDARD</b>
 <b>UNE-EN ISO 10545-14</b> STAIN RESISTANCE - GREEN AGENT IN LIGHT OIL	<b>5</b>
STAIN RESISTANCE - IODINE SOLUTION IN ALCOHOL	<b>5</b>
STAIN RESISTANCE - OLIVE OIL	<b>5</b>

Ancona 2.0 Grey Parquet



# SIZES

## TILES

Height	Width	Thickness	Nominal
8"	30"	3/8"	Yes
8"	48"	3/8"	Yes
24"	24"	3/8"	Yes

## FINISHES



Polished



Matte

---

## ORDER NOTE

All sizes are nominal and in inches. Special cut sizes and additional trim pieces are available upon meeting a required minimum order quantity.

Parquet is only available in 24" x 24" in Chestnut, Grey and Maple.

INTERIORS	EXTERIORS	WALLS
APPLICATIONS		
FLOORS		HIGH-TRAFFIC



31% PRE-CONSUMER  
RECYCLED CONTENT



DCOF .42 – PASS  
HONED + BRUSHED FINISH

